PRODUCT DATA		
RESCO [®] PRODUCTS, INC. Brand Name: MIX 05-		
CORDIERITE Physical properties shown are averages based on stan ASTM test methods used where applicable		ast sizes.
Maximum Service Temperature: 2400°F (1316°C)		
Bulk Density (pcf)	124	(1.99 g/cm ³)
Modulus of Rupture (Ib/in ²)	800	(56 kg/cm ²)
Coefficient of Thermal Expansion (x 10 ⁻⁶ in/in/°C)		2.7
Porosity (%) 26		
<u>Typical Chemical Analysis (%)</u> (Calcined Basis)		
Alumina (Al_2O_3)	44.1	
Silica (SiO ₂)	47.3	
Iron Oxide (Fe ₂ O ₃)	1.5	
Titania (TiO ₂)	1.4	
Lime (CaO)	0.1	
Magnesia (MgO) Alkalis (Na ₂ O+K ₂ O)	5.3 0.3	
Brand Code: 5158		
The properties shown on this data sheet represent typical average res otherwise noted) conducted under controlled condition (using standa be guaranteed specifications. Properties are subject to normal manufa Products, Inc. reserves the right to modify the properties and specifica	rd rectangula acturing stati	ar shapes), and should not be considered to stical standard deviation ranges, and Resco

RESCO PRODUCTS disclaims any express or implied warranties based on this sheet.

02/23/17 is the date that this data sheet was updated. Check with your RESCO sales representative or RESCO website to determine you have the current sheet.

One Robinson Plaza - Suite 300, 6600 Steubenville Pike, Pittsburgh, PA, 15205 Phone: 888-283-5505