

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 04/26/2022 Revision date: 04/26/2022 Supersedes: 09/08/2020

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Adacor 70 Dip & Trowel

CAS-No. : Mixture
Product code : 0104, 0105

Other means of identification : Alumina-Silicate Wet Air Set Mortar-Slurry

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Recommended use : Industrial use

1.3. Supplier

Resco Products. Inc.

One Robinson Plaza, Suite 300

6600 Steubenville Pike

Pittsburgh, PA 15205 - United States

412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 2B H320 Causes eye irritation

Carcinogenicity Category 1A H350 May cause cancer (After drying or heating, Inhalation)

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H315 - Causes skin irritation

H319 - Causes serious eye irritation

H350 - May cause cancer (After drying or heating, Inhalation)

Precautionary statements (GHS US) : P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear eye protection, protective gloves, protective clothing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
aluminium oxide, non-fibrous	(CAS-No.) 1344-28-1	50 – 75	Not classified
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions	(CAS-No.) 1344-09-8	20 – 50	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
quartz	(CAS-No.) 14808-60-7	1 – 5	Carc. 1A, H350
cristobalite	(CAS-No.) 14464-46-1	0.1 – 0.5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

04/26/2022 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before

reuse

First-aid measures after eve contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Most important symptoms and effects (acute and delayed)

: Based on available data, the classification criteria are not met. Potential Adverse human health effects and

symptoms

: After drying or heating. May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/effects after skin contact Causes skin irritation. Symptoms/effects after eve contact Causes serious eve irritation.

Immediate medical attention and special treatment, if necessary

No additional information available

Symptoms/effects after inhalation

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media No unsuitable extinguishing media known.

5.2 Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering

environment.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : If spilled, may cause the floor to be slippery.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop release.

6.2. **Environmental precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Plug the leak, cut off the supply.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes. Avoid contact with skin.

Hygiene measures Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

Conditions for safe storage, including any incompatibilities

: Store in original container. Keep container closed when not in use. Storage conditions

Incompatible products : Strong bases. Strong acids.

SECTION 8: Exposure controls/personal protection

Control parameters

Adacor 70 Dip & Trowel (Mixture) No additional information available sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8) No additional information available cristobalite (14464-46-1) **USA - ACGIH - Occupational Exposure Limits** ACGIH TWA (mg/m3) 0.025 mg/m3 respirable dust **USA - OSHA - Occupational Exposure Limits** 0.05 mg/m3 respirable dust OSHA PEL (TWA) (mg/m3) aluminium oxide, non-fibrous (1344-28-1) **USA - ACGIH - Occupational Exposure Limits** ACGIH TWA (mg/m3) 1 mg/m3 respirable dust

04/26/2022 EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

quartz (14808-60-7)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (mg/m³) 0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)		
USA - OSHA - Occupational Exposure Limits		
Local name	Silica, crystalline quartz, respirable dust	
OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ respirable dust	
Remark (OSHA)	(3) See Table Z-3.	

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountain with clean water.

: Not applicable

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

After air drying or heating. Dust when sawing or tear out. Wear appropriate mask

Other information:

Odor threshold

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Slurry.
Color : Gray
Odor : earthy

pH : > 10 Melting point : $> 2000 \, ^{\circ}F$

Freezing point : ≈ 32 °F Not applicable

Boiling point : Not applicable

Critical temperature : Not applicable

Critical pressure : Not applicable

Flash point : Not applicable

Relative evaporation rate (butyl acetate=1) : Not applicable

Relative evaporation rate (ether=1) : Not applicable

Flammability (solid, gas) : None

Non flammable.

Vapor pressure : Not applicable

Vapor pressure at 50 °C : Not applicable

Relative vapor density at 20 °C : No data available

Relative density : ≈ 1.7

Solubility : Moderately soluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : Not applicable : No data available Decomposition temperature No data available Viscosity, kinematic Viscosity, dynamic : Not Applicable **Explosion limits** : Not applicable Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

04/26/2022 EN (English US) 3/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity	
10.1. Reactivity	
Air Setting.	
10.2. Chemical stability	
Not established.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
No additional information available	
10.5. Incompatible materials Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
	ous decomposition products should not be produced.
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55	5%. aqueous solutions (1344-09-8)
LD50 oral rat	> 2000 mg/kg (Rat, Oral)
aluminium oxide, non-fibrous (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female,
EBSO Graffat	Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value,
	Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation	Causes skin irritation.
	pH: > 10
Serious eye damage/irritation	Causes eye irritation.
Despirator or alsia consistration	pH: > 10 Not classified
Respiratory or skin sensitization Germ cell mutagenicity	Not classified
Carcinogenicity	May cause cancer (After drying or heating, Inhalation).
quartz (14808-60-7)	may badde carbon (rater drying of floating, finitiation).
	4. Carainagania ta humana
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	Not classified
STOT-single exposure	Not classified Not classified
STOT-repeated exposure	Not classified
Aspiration hazard Viscosity, kinematic	No data available
Potential Adverse human health effects and	Based on available data, the classification criteria are not met.
symptoms	based on available data, the classification effects are not met.
	After drying or heating. May cause cancer by inhalation. Danger of serious damage to health by
-,···	prolonged exposure through inhalation.
Symptoms/effects after skin contact	Causes skin irritation.
, ,	Causes serious eye irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55	5% aqueous solutions (1344-09-8)
	210 mg/l (06 h. Prochydenie rerie. Pure substance)

sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)		
LC50 fish 1 210 mg/l (96 h, Brachydanio rerio, Pure substance)		
EC50 Daphnia 1 216 mg/l (96 h, Daphnia magna, Pure substance)		
aluminium oxide, non-fibrous (1344-28-1)		
LC50 fish 1	> 100 mg/l (96 h, Salmo trutta, Literature study)	
EC50 Daphnia 1 > 100 mg/l (48 h, Daphnia magna, Literature study)		

12.2. Persistence and degradability

Adacor 70 Dip & Trowel (Mixture)		
Persistence and degradability Not established.		
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)		
Persistence and degradability	ability Biodegradability: not applicable.	
Chemical oxygen demand (COD)	l oxygen demand (COD) Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	

04/26/2022 EN (English US) 4/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

According to Federal Register / Vol. 77, No. 30 / Moriday, Maron 20, 2012 / Raica			
cristobalite (14464-46-1)			
Persistence and degradability Mineral. Not ap	plicable.		
Chemical oxygen demand (COD) Not applicable			
ThOD Not applicable			
BOD (% of ThOD) Not applicable			
aluminium oxide, non-fibrous (1344-28-1)			
Persistence and degradability Not applicable.			
Chemical oxygen demand (COD) Not applicable			
ThOD Not applicable			
quartz (14808-60-7)			
Persistence and degradability Not applicable.			
Biochemical oxygen demand (BOD) Not applicable			
Chemical oxygen demand (COD) Not applicable			
ThOD Not applicable			
12.3. Bioaccumulative potential			
Adacor 70 Dip & Trowel (Mixture)			
Bioaccumulative potential Not established	l.		
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)			
Bioaccumulative potential No bioaccumul	ation data available.		
cristobalite (14464-46-1)			
Bioaccumulative potential No data availab	ole.		
aluminium oxide, non-fibrous (1344-28-1)			
Bioaccumulative potential No data availab	ole.		
quartz (14808-60-7)			
Bioaccumulative potential No data availab	ole.		
12.4. Mobility in soil			
	sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)		
	on mobility of the component(s) available.		
cristobalite (14464-46-1)			
Ecology - soil No data availat	ole.		
aluminium oxide, non-fibrous (1344-28-1)	·		
	No in the literature		
	ole in the literature		
Ecology - soil No data available 12.5. Other adverse effects	אנ.		
Effect on the global warming None known			
Other information : Avoid release to the environment.			

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated
Transport by sea
Not regulated

Air transport Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Adacor 70 Dip & Trowel (Mixture)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)

04/26/2022 EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adacor 70 Dip & Trowel (Mixture)		
Not subject to reporting requirements of the United States SARA Section 313		
Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Alumin		
	oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing,	

processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

15.2. International regulations

CANADA

cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Adacor 70 Dip & Trowel (Mixture)	
U.S California - Proposition 65 - Other	This product contains crystalline silica, a chemical known to the state of California to
information	cause cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (1446	4-46-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

quartz (14808-60-7)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/26/2022

Other information : Report language name. English. In the event of any conflict between English and other

language versions, the English version shall prevail.

Full text of H-phrases:

H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

04/26/2022 EN (English US) 6/6