

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 7/18/2022 Revision date: 7/18/2022 Supersedes: 1/5/2018

SECTION 1: Identification				
1.1. Identification				
Product form Product name CAS-No. Product code Other means of identification	: Mixture : KD30-DOL : Mixture : 5031 : Dolomite Burned Brid	:k		
1.2. Recommended use and restrictions on u				
	: Refractory Brick : Industrial use			
1.3. Supplier				
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States 412-494-4491 SDS@RescoProducts.com - WWW.RescoProducts.cc	om			
1.4. Emergency telephone number				
· · · ·	EMERGENCY ONLY		& Canada 1-800)-424-9300
	Outside USA & Cana	ida +1 703-741-5970		
SECTION 2: Hazard(s) identification				
2.1. Classification of the substance or mixtu	re			
GHS US classification Skin corrosion/irritation Category 1A Carcinogenicity Category 1A Full text of H statements : see section 16	H314 H350			and eye damage vhen sawing or tear out, Inhalation)
2.2. GHS Label elements, including precaution	onary statements			
GHS US labeling Hazard pictograms (GHS US)				
Precautionary statements (GHS US)	 Danger H314 - Causes severe skin burns and eye damage H350 - May cause cancer (Dust when sawing or tear out, Inhalation) P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear Safety shoes, eye protection, protective gloves, protective clothing. P223 - Do not allow contact with water. Avoid contact with the skin and the eyes P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Gently wash with plenty of soap and water. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting. P260 - Do not breathe Dust when sawing or tear out. 			
2.3. Other hazards which do not result in cla	ssification			
No additional information available				
2.4. Unknown acute toxicity (GHS US) Not applicable				
SECTION 3: Composition/Information of	ingredients			
	Tingrealents			
3.1. Substances				
Not applicable 3.2. Mixtures				
Name		Product identifier	%	GHS US classification
Magnesium Oxide		CAS-No.: 1309-48-4	50 – 75	Not classified
calcium oxide		CAS-No.: 1305-78-8	20 – 50	Skin Corr. 1A, H314
cristobalite		CAS-No.: 14464-46-1	0.1 – 0.5	Carc. 1A, H350
7/18/2022 (Revision date)	EN (Engl	lish US)		1/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see se	action 16
SECTION 4: First-aid measures	
4.1. Description of first aid measures	· Cet medical advice/attention if you feel unwell
First-aid measures general First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact	 Get medical advice/attention if you feel unwell. Dust when sawing or tear out. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth.
4.2. Most important symptoms and effects (
Symptoms/effects after skin contact Symptoms/effects after eye contact	 May cause moderate irritation. Causes serious eye irritation.
4.3. Immediate medical attention and specia	al treatment, if necessary
No additional information available	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	
Suitable extinguishing media Unsuitable extinguishing media	: Carbon dioxide. Dry powder. Sand.
5.2. Specific hazards arising from the chem	: Do not use extinguishing media containing water.
Fire hazard	: In contact with water releases flammable gas. In case of fire, use sand, "never use water".
5.3. Special protective equipment and preca	
Firefighting instructions	: In case of fire, use powder extinguisher, "never use water". In case of fire, never use water.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measur	es
6.1. Personal precautions, protective equip	ment and emergency procedures
6.1.1. For non-emergency personnel Protective equipment Emergency procedures 6.1.2. For emergency responders	 Protective gloves. Safety glasses. Safety shoes. Protective clothing. Avoid contact with skin and eyes.
Protective equipment	: Do not attempt to take action without suitable protective equipment.
6.2. Environmental precautions	
No additional information available	
6.3. Methods and material for containment a	
For containment Methods for cleaning up	 On land, sweep or shovel into suitable containers. Collect spillage.
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Avoid contact with eyes. Contact lenses should be removed. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
7.2. Conditions for safe storage, including a	any incompatibilities
Storage conditions	: Store this product in a dry location where it can be protected from the elements. Protect from
Incompatible products	 moisture. Acids; reactive fluoridated, brominated, or phosphorous compounds; aluminum (may form hydrogen gas); reactive metals; organic acid anhydrides; nitro-organic compounds; interhalogenated compounds.
SECTION 8: Exposure controls/persona	al protection
8.1. Control parameters	
KD30-DOL (Mixture)	
No additional information available	
Magnesium Oxide (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA	10 mg/m ³ inhalable dust

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium Oxide (1309-48-4) USA - OSHA - Occupational Exposure Limits			
OSHA PEL (TWA) [1]	10 mg/m ³ respirable dust		
calcium oxide (1305-78-8)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	2 mg/m ³		
cristobalite (14464-46-1)			
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA	0.025 mg/m ³ respirable dust		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL (TWA) [1]	0.05 mg/m ³ respirable dust		
8.2. Appropriate engineering controls			
Appropriate engineering controls	: Dust when sawing or tear out. Provide adequate ventilation to minimize dust concentrations.		
8.3. Individual protection measures/Persona	I protective equipment		
Personal protective equipment: Avoid all unnecessary exposure.			
Hand protection:			
Impermeable protective gloves			
Eye protection:			
Chemical goggles or safety glasses			
Skin and body protection:			
Wear suitable protective clothing ;Safety shoes	Wear suitable protective clothing ;Safety shoes		
Respiratory protection:			
Dust when sawing or tear out. Wear appropriate mask			
SECTION 9: Physical and chemical properties			
9.1. Information on basic physical and chemical properties			
Physical state	: Solid		
Appearance	: Solid in various shapes.		
Appearance Color	: Solid in various shapes. : brown		
Appearance	: Solid in various shapes.		
Appearance Color Odor Odor threshold pH	 Solid in various shapes. brown odorless No data available No data available 		
Appearance Color Odor Odor threshold pH Melting point	 Solid in various shapes. brown odorless No data available No data available > 2500 °F 		
Appearance Color Odor Odor threshold pH Melting point Freezing point	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available No data available No data available No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1)	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas)	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C Relative density	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 2.65 – 2.85 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C Relative density Solubility	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available So data available No data available So data available No data available Reacts with water to form Ca(OH)2, Mg(OH)2, and heat. 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		
Appearance Color Odor Odor threshold pH Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Uiscosity, kinematic Viscosity, kinematic Explosion limits Explosive properties	 Solid in various shapes. brown odorless No data available No data available > 2500 °F No data available 		

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts exothermically with water (moisture). Reacts with water to form Ca(OH)2, Mg(OH)2, and heat. Reacts with acids to form calcium salts while generating heat.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability	
No additional information available	
10.3. Possibility of hazardous reactions	
No additional information available	
10.4. Conditions to avoid	
Water, humidity.	
10.5. Incompatible materials	
Acids.	
10.6. Hazardous decomposition products	
Thermal decomposition generates : Carbon monoxide. SECTION 11: Toxicological information	Carbon dioxide.
11.1. Information on toxicological effects	
	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation) :	Not classified
Magnesium Oxide (1309-48-4)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)
calcium oxide (1305-78-8)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2500 mg/kg body weight (EU Method B.3: Acute toxicity (dermal), 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 6.04 mg/l (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Experimental value, Inhalation (dust), 15 day(s))
Skin corrosion/irritation :	Causes severe skin burns.
Magnesium Oxide (1309-48-4)	
рН	11 (10 %)
calcium oxide (1305-78-8)	
рН	12.5 (0.13 %, 20 °C)
cristobalite (14464-46-1)	
рН	6 – 7
Serious eye damage/irritation :	Assumed to cause serious eye damage
Magnesium Oxide (1309-48-4)	
pH	11 (10 %)
calcium oxide (1305-78-8)	
pH	12.5 (0.13 %, 20 °C)
cristobalite (14464-46-1)	
рН	6 - 7
	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	May cause cancer (Dust when sawing or tear out, Inhalation).
Reproductive toxicity :	Not classified Not classified
STOT-single exposure : STOT-repeated exposure :	Not classified
Aspiration hazard :	Not classified
Viscosity, kinematic :	No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium Oxide (1309-48-4)		
Viscosity, kinematic	Not applicable (solid)	
calcium oxide (1305-78-8)		
Viscosity, kinematic	Not applicable (solid)	
Symptoms/effects after skin contact Symptoms/effects after eye contact	: May cause moderate irritation. : Causes serious eye irritation.	
SECTION 12: Ecological information		
12.1. Toxicity		
calcium oxide (1305-78-8)		
LC50 - Fish [1]	50.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Read-across, GLP)	
EC50 - Crustacea [1]	49.1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, Locomotor effect)	
ErC50 algae	184.57 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)	
12.2. Persistence and degradability		
Magnesium Oxide (1309-48-4)		
Persistence and degradability	Not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
calcium oxide (1305-78-8)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
cristobalite (14464-46-1)		
Persistence and degradability	Mineral. Not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
12.3. Bioaccumulative potential		
Magnesium Oxide (1309-48-4)		
Bioaccumulative potential	No bioaccumulation data available.	
calcium oxide (1305-78-8)		
Bioaccumulative potential	Not bioaccumulative.	
cristobalite (14464-46-1)		
Bioaccumulative potential	No data available.	
12.4. Mobility in soil		
Magnesium Oxide (1309-48-4)		
Surface tension	No data available in the literature	
Ecology - soil	No data available.	
calcium oxide (1305-78-8)		
Surface tension	No data available in the literature	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

calcium oxide (1305-78-8)				
No (test) data on mobility of the substance available.				
cristobalite (14464-46-1)				
No data available.				
2.5. Other adverse effects				
No additional information available				
SECTION 14: Transport information				
Department of Transportation (DOT) In accordance with DOT Not regulated Transportation of Dangerous Goods Not regulated				
Transport by sea Not regulated				
Air transport				
s Active on the United St	tates Environmental Pro	tection Agency Toxic S	ubstances Control Act	
15.2. International regulations				
st)				
st)				
st)				
st)				
,				
,				
,				
st)	rystalline silica, a chemi nation go to WWW.P65V	cal known to the state Varnings.ca.gov	of California to cause	
st)	rystalline silica, a chemi nation go to WWW.P65V	cal known to the state Varnings.ca.gov	of California to cause	
st)	u.S California - Proposition 65 - Reproductive Toxicity - Male	cal known to the state Varnings.ca.gov No significant risk level (NSRL)	of California to cause Maximum allowable dose level (MADL)	
This product contains of cancer.For more inform U.S California - Proposition 65 - Reproductive Toxicity	U.S California - Proposition 65 - Reproductive Toxicity	Varnings.ca.gov No significant risk	Maximum allowable	
This product contains of cancer.For more inform U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Varnings.ca.gov No significant risk	Maximum allowable	
	No data available.	No data available.	No data available.	

Magnesium Oxide (1309-48-4)

U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component		State or local regulations
calcium oxide (13	05-78-8)	U.S New Jersey - Right to Know Hazardous Substance List
Cristobalite (1446	4-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
SECTION 16: Other information according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
Other information		
Full text of H-phrases		
H314	Causes severe skin burns and eye damage	
H350	May cause cancer	

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.