

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 05/17/2021 Supersedes: 08/31/2017 Issue date: 05/17/2021

### **SECTION 1: Identification**

Identification

Product form Mixture Product name Quikturn 56 SCG CAS-No. Mixture Product code 0738

Other means of identification Alumina-Silicate Cement Bonded Castable

Recommended use and restrictions on use 1.2.

Use of the substance/mixture : Refractory : Industrial use Recommended use

**Supplier** 

Resco Products. Inc.

One Robinson Plaza, Suite 300

6600 Steubenville Pike

Pittsburgh, PA 15205 - United States

412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

**Emergency telephone number** 

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

**GHS US classification** 

Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 2B H320 Causes eye irritation

Carcinogenicity Category 1A H350 May cause cancer (Inhalation)

Full text of H statements: see section 16

#### 2.2. GHS Label elements, including precautionary statements

**GHS US labeling** 

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) H315 - Causes skin irritation H320 - Causes eye irritation H350 - May cause cancer (Inhalation)

: P280 - Wear eye protection, Dust respirator, protective gloves. Precautionary statements (GHS US)

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P260 - Do not breathe dust.

#### Other hazards which do not result in classification

No additional information available

#### **Unknown acute toxicity (GHS US)** 2.4.

Not applicable

### **SECTION 3: Composition/Information on ingredients**

Not applicable

### **Mixtures**

Name	Product identifier	%	GHS US classification
silicon carbide	(CAS-No.) 409-21-2	50 – 75	Carc. 1B, H350
aluminium oxide, non-fibrous	(CAS-No.) 1344-28-1	10 – 20	Not classified
Calcium Aluminate Cement	(CAS-No.) 65997-16-2	1 – 5	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
quartz	(CAS-No.) 14808-60-7	0.5 – 1	Carc. 1A, H350
cristobalite	(CAS-No.) 14464-46-1	0.1 – 0.5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

05/17/2021 EN (English US) Page 1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact Wash with plenty of soap and water. Wash contaminated clothing before reuse.

First-aid measures after eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure

through inhalation. Causes skin irritation. Causes eye irritation.

Symptoms/effects after eye contact Immediate medical attention and special treatment, if necessary

No additional information available

Symptoms/effects after skin contact

### **SECTION 5: Fire-fighting measures**

### Suitable (and unsuitable) extinguishing media

Suitable extinguishing media Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media In case of fire, all extinguishing media allowed.

Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering

environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

**Emergency procedures** : Do not breathe dust.

For emergency responders 6.1.2.

Protective equipment

Equip cleanup crew with proper protection.

**Emergency procedures** : Ventilate area.

**Environmental precautions** 

Prevent entry to sewers and public waters.

Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

### **SECTION 7: Handling and storage**

### Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid raising dust.

Avoid contact with skin and eyes. Do not breathe dust.

Hygiene measures Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

Conditions for safe storage, including any incompatibilities

Storage conditions Store this product in a dry location where it can be protected from the elements.

Incompatible products Strong bases. Strong acids.

### **SECTION 8: Exposure controls/personal protection**

### **Control parameters**

Quikturn 56 SCG (Mixture)  No additional information available  Calcium Aluminate Cement (65997-16-2)				
			No additional information available	
			cristobalite (14464-46-1)	
USA - ACGIH - Occupational Exposure Limits				
ACGIH TWA (mg/m³) 0.025 mg/m³ respirable dust				
USA - OSHA - Occupational Exposure Limits				
OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ respirable dust			
silicon carbide (409-21-2)				
USA - ACGIH - Occupational Exposure Limits  ACGIH TWA (mg/m³)  3 mg/m³ (Silicon carbide, nonfibrous; USA; Time-weighted average exposure limit 8 h  TLV - Adopted Value; Respirable fraction. The value is for particulate matter containing				

05/17/2021 EN (English US) 2/7

no asbestos and < 1% crystalline silica.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (mg/m³)	1 mg/m³ respirable dust	
quartz (14808-60-7)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (mg/m³)  0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure h; TLV - Adopted Value; Respirable fraction)		
USA - OSHA - Occupational Exposure Limits		
Local name Silica, crystalline quartz, respirable dust		
OSHA PEL (TWA) (mg/m³)	OSHA PEL (TWA) (mg/m³) 0.05 mg/m³ respirable dust	
Remark (OSHA) (3) See Table Z-3.		

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Avoid all unnecessary exposure.

### Hand protection:

Wear protective gloves.

### Eye protection:

Chemical goggles or safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Wear appropriate mask

### Other information:

Do not eat, drink or smoke during use.

### **SECTION 9: Physical and chemical properties**

9.1.	Information on basic physical and	d chemi	cal properties
Physica	al state	:	Solid
Appear Color	rance	:	Granular mixture. dark gray
Odor		:	earthy
Odor th	nreshold	:	Not applicable
рН		:	No data available
Melting	point	:	> 2500 °F
Freezin	ng point	:	Not applicable
Boiling	point	:	Not applicable
	temperature pressure point	:	Not applicable Not applicable Not applicable
Relative	e evaporation rate (butyl acetate=1)	:	Not applicable
	e evaporation rate (ether=1) ability (solid, gas)	:	Not applicable Non flammable.
Vapor p	pressure	:	Not Applicable
	pressure at 50 °C e vapor density at 20 °C	:	Not Applicable No data available

Relative density :  $\approx 2.4$ 

Solubility : Slightly soluble. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : Not applicable Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : Not Applicable Explosion limits : Not applicable Explosive properties : No data available Oxidizing properties : No data available

05/17/2021 EN (English US) 3/7

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

-	-
9.2.	Other information
No add	litional information available
SECT	TON 10: Stability and reactivity
10.1.	Reactivity
Hydrau	ilic setting.
10.2.	Chemical stability

Stable under normal conditions of use. Possibility of hazardous reactions

Not established.

10.4. **Conditions to avoid** 

Avoid dust formation.

10.5. Incompatible materials

Strong acids. Strong bases.

**Hazardous decomposition products** 

No additional information available

### **SECTION 11: Toxicological information**

11.1.	Information on toxicological effects	3	
Acute t	toxicity (oral)	:	Not classified
Acute t	toxicity (dermal)	:	Not classified
Acute t	toxicity (inhalation)	:	Not classified

silicon carbide (409-21-2)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)

aluminium oxide, non-fibrous (1344-28-1)	luminium oxide, non-fibrous (1344-28-1)		
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)		
LC50 Inhalation - Rat	7.6 mg/l air (Equivalent or similar to OECD 403, 1 h, Rat, Male, Experimental value, Inhalation (aerosol))		
Skin corrosion/irritation : Causes skin irritation.			

Serious eye damage/irritation : Causes eye irritation. Respiratory or skin sensitization Not classified Germ cell mutagenicity Not classified

Carcinogenicity May cause cancer (Inhalation).

silicon carbide (409-21-2)	
IARC group	2A - Probably carcinogenic to humans

quartz (14808-60-7)		
	IARC group	1 - Carcinogenic to humans
	Reproductive toxicity	Not classified
	STOT-single exposure Not classified	

: Not classified STOT-repeated exposure Aspiration hazard Not classified No data available Viscosity, kinematic Potential Adverse human health effects and

: Based on available data, the classification criteria are not met. symptoms

Symptoms/effects after inhalation May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.

Causes skin irritation. Symptoms/effects after skin contact Symptoms/effects after eye contact : Causes eye irritation.

### **SECTION 12: Ecological information**

### Toxicity

No additional information available

#### Persistence and degradability 12.2.

Quikturn 56 SCG (Mixture)	
Persistence and degradability	Not established.
cristobalite (14464-46-1)	
Persistence and degradability	Mineral. Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

05/17/2021 EN (English US) 4/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

silicon carbide (409-21-2)			
Persistence and degradability	Biodegradability: not applicable.		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
BOD (% of ThOD)	Not applicable		
aluminium oxide, non-fibrous (1344-28-1)			
Persistence and degradability	Not applicable.		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
quartz (14808-60-7)			
Persistence and degradability	Not applicable.		
Biochemical oxygen demand (BOD)	Not applicable		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
12.3. Bioaccumulative potential			
Quikturn 56 SCG (Mixture)			
Bioaccumulative potential	Not established.		
cristobalite (14464-46-1)			
Bioaccumulative potential	No data available.		
silicon carbide (409-21-2)			
Bioaccumulative potential Bioaccumulation: not applicable.			
aluminium oxide, non-fibrous (1344-28-1)			
Bioaccumulative potential No data available.			
·	The data available.		
quartz (14808-60-7)	No data available.		
Bioaccumulative potential	NO data available.		
12.4. Mobility in soil			
cristobalite (14464-46-1)			
Ecology - soil	No data available.		
aluminium oxide, non-fibrous (1344-28-1)			
Ecology - soil	No data available.		
12.5. Other adverse effects			
Effect on the global warming	None known		
Other information SECTION 13: Disposal considerations	: No other effects known.		
·	• <del></del>		
13.1. Disposal methods Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.		
Ecology - waste materials	: Avoid release to the environment.		
SECTION 14: Transport information			
Department of Transportation (DOT)			
In accordance with DOT			
Not regulated			

Not regulated Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

05/17/2021 EN (English US) 5/7

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

### **Quikturn 56 SCG (Mixture)**

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note

Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

### 15.2. International regulations

#### **CANADA**

#### Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

### cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

### silicon carbide (409-21-2)

Listed on the Canadian DSL (Domestic Substances List)

### aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

**National regulations** 

#### silicon carbide (409-21-2)

Listed on IARC (International Agency for Research on Cancer)

#### quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

Quikturn 56 SCG (Mixture)		
U.S California - Proposition 65 - Other	This product contains crystalline silica, a chemical known to the state of California to	
information	cause cancer. For more information go to WWW.P65Warnings.ca.gov	

cristobalite (14464-46-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

quartz (14808-60-7)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
silicon carbide (409-21-2)	U.S New Jersey - Right to Know Hazardous Substance List
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/17/2021

Other information : Report language name. English. In the event of any conflict between English and other

language versions, the English version shall prevail.

05/17/2021 EN (English US) 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-phrases:

H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

05/17/2021 EN (English US) 7/7