

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 12/11/2022 Revision date: 12/11/2022 Supersedes: 10/8/2020

# **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture

Product name : Quikturn AZS PC H

CAS-No. : Mixture Product code : 4423

Other means of identification : Alumina-Silicate Cement Bonded Castable

### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Recommended use : Industrial use

#### 1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA, 15205
United States
412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

### 1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

### **SECTION 2: Hazard(s) identification**

### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 2B H320 Causes eye irritation

Carcinogenicity Category 1A H350 May cause cancer (Inhalation)

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US)

Hazard statements (GHS US) : H315 - Causes skin irritation H320 - Causes eye irritation

H350 - May cause cancer (Inhalation)

Precautionary statements (GHS US) : P280 - Wear eye protection, Dust respirator, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P260 - Do not breathe dust.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Radioactivity: In c

Radioactivity: In common with many naturally occurring mineral products zirconia contains very low levels of naturally occurring radioactive elements, principally uranium, thorium and radium. The principal radiation hazard is due to inhalation of any dust, while a secondary lesser external hazard exists through gamma radiation.

# 2.4. Unknown acute toxicity (GHS US)

No additional information available

### **SECTION 3: Composition/Information on ingredients**

# 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Zirconia	CAS-No.: 1314-23-4	10 – 20	Not classified
aluminium oxide, non-fibrous	CAS-No.: 1344-28-1	10 – 20	Not classified

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Calcium Aluminate Cement	CAS-No.: 65997-16-2		Skin Irrit. 2, H315 Eye Irrit. 2B, H320
silicon carbide	CAS-No.: 409-21-2	5 – 10	Carc. 1B, H350
quartz	CAS-No.: 14808-60-7	0.1 - 0.5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

Based on available data, the classification criteria are not met.

symptoms

Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure

through inhalation.
: Causes skin irritation.
: Causes eye irritation.

Symptoms/effects after eye contact : Causes eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

Symptoms/effects after skin contact

### **SECTION 5: Fire-fighting measures**

# 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Not flammable.

# 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Do not breathe dust.

**6.1.2. For emergency responders**Protective equipment

: Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

# 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid raising dust.

Avoid contact with skin and eyes. Do not breathe dust.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store this product in a dry location where it can be protected from the elements.

Incompatible products : Strong bases. Strong acids.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

12/11/2022 (Revision date) EN (English US) 2/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quikturn AZS PC H (Mixture)			
No additional information available			
Calcium Aluminate Cement (65997-16-2)			
No additional information available			
silicon carbide (409-21-2)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	3 mg/m³ (Silicon carbide, nonfibrous; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica.		
aluminium oxide, non-fibrous (1344-28-1)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	1 mg/m³ respirable dust		
Zirconia (1314-23-4)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	5 mg/m³ As Zr		
USA - OSHA - Occupational Exposure Limits	USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) [1]	5 mg/m³ As Zr		
quartz (14808-60-7)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)		
USA - OSHA - Occupational Exposure Limits			
Local name	Silica, crystalline quartz, respirable dust		
OSHA PEL (TWA) [1]	0.05 mg/m³ respirable dust		
Remark (OSHA)	(3) See Table Z-3.		
8.2. Appropriate engineering controls			
	Provide adequate ventilation to minimize dust concentrations.		
8.3. Individual protection measures/Personal protective equipment Personal protective equipment:			
Avoid all unnecessary exposure.			
Hand protection:			
Wear protective gloves.			
Eye protection:			
Chemical goggles or safety glasses			
Skin and body protection:			

Hand protection:
Wear protective gloves.
Eye protection:
Chemical goggles or safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
Wear appropriate mask

# Other information:

Do not eat, drink or smoke during use.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state Solid

: Granular mixture. Appearance

12/11/2022 (Revision date) EN (English US) 3/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Hydraulic setting.

# 10.2. Chemical stability

Stable under normal conditions of use.

# 10.3. Possibility of hazardous reactions

Not established.

# 10.4. Conditions to avoid

Avoid dust formation.

# 10.5. Incompatible materials

Strong acids. Strong bases.

# 10.6. Hazardous decomposition products

No additional information available

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

silicon carbide (409-21-2)		
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))	
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)	
aluminium oxide, non-fibrous (1344-28-1)		
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))	

Skin corrosion/irritation : Causes skin irritation.

Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

silicon carbide (409-21-2)	
рН	Not applicable (non-soluble in water), CIPAC MT 75: Determination of pH
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
pH	6 – 7
Serious eye damage/irritation :	Causes eye irritation.
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
silicon carbide (409-21-2)	
рН	Not applicable (non-soluble in water), CIPAC MT 75: Determination of pH
aluminium oxide, non-fibrous (1344-28-1)	
pH	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 – 7
. ,	Not classified
Germ cell mutagenicity : Carcinogenicity :	Not classified
silicon carbide (409-21-2)	May cause cancer (Inhalation).
IARC group	2A - Probably carcinogenic to humans
quartz (14808-60-7)	2.1 Trobably carolinggone to Hamario
IARC group	1 - Carcinogenic to humans
Reproductive toxicity :	Not classified
STOT-single exposure :	Not classified
STOT-repeated exposure :	Not classified
Aspiration hazard :	Not classified
Viscosity, kinematic : silicon carbide (409-21-2)	Not Applicable
Viscosity, kinematic	Not applicable (solid)
aluminium oxide, non-fibrous (1344-28-1)	The application (cons)
	Not applicable (solid)
Viscosity, kinematic  Potential Adverse human health effects and :	Not applicable (solid)  Based on available data, the classification criteria are not met.
symptoms	
Symptoms/effects after inhalation :	May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure
Symptoms/effects after skin contact :	through inhalation. Causes skin irritation.
Symptoms/effects after eye contact :	Causes eye irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
silicon carbide (409-21-2)	
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 48 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
aluminium oxide, non-fibrous (1344-28-1)	
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability		
Quikturn AZS PC H (Mixture)		
Persistence and degradability	Not established.	
silicon carbide (409-21-2)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
aluminium oxide, non-fibrous (1344-28-1)		
Persistence and degradability	Not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
quartz (14808-60-7)		
Persistence and degradability	Not applicable.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
12.3. Bioaccumulative potential		
Quikturn AZS PC H (Mixture)		
Bioaccumulative potential	Not established.	
silicon carbide (409-21-2)		
Bioaccumulative potential	Not bioaccumulative.	
aluminium oxide, non-fibrous (1344-28-1)		
Bioaccumulative potential	No data available.	
quartz (14808-60-7)		
Bioaccumulative potential	No data available.	
12.4. Mobility in soil		
silicon carbide (409-21-2)		
Surface tension	No data available in the literature	
Ecology - soil	Low potential for adsorption in soil.	
aluminium oxide, non-fibrous (1344-28-1)		
Surface tension	No data available in the literature	
Ecology - soil	No data available.	
12.5. Other adverse effects		
Effect on the global warming :	None known	
Other information :	No other effects known.	

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

# **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

**Department of Transportation (DOT)** 

In accordance with DOT

Not regulated

**Transportation of Dangerous Goods** 

Not regulated
Transport by sea
Not regulated
Air transport

Not regulated

**SECTION 15: Regulatory information** 

# 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)
--

Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

### 15.2. International regulations

#### CANADA

### Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

### silicon carbide (409-21-2)

Listed on the Canadian DSL (Domestic Substances List)

### aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

### Zirconia (1314-23-4)

Listed on the Canadian DSL (Domestic Substances List)

**EU-Regulations** 

No additional information available

**National regulations** 

# silicon carbide (409-21-2)

Listed on IARC (International Agency for Research on Cancer)

### quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

#### 15.3. US State regulations

### **Quikturn AZS PC H (Mixture)**

U.S. - California - Proposition 65 - Other information

This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov

quartz (14808-60-7)					
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity		
		- Female	- Male		
Yes	No	No	No		

Component	State or local regulations
silicon carbide (409-21-2)	U.S New Jersey - Right to Know Hazardous Substance List
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
	Substance List; U.S Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 12/11/2022

Other information : Report language name. English. In the event of any conflict between English and other language

versions, the English version shall prevail.

Full text of H-phrases	
H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

12/11/2022 (Revision date) EN (English US) 7/7