

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 07/19/2021 Revision date: 07/19/2021 Supersedes: 04/14/2020

### **SECTION 1: Identification**

1.1. Identification

Product form : Mixture
Product name : Rescocast 7
CAS-No. : Mixture
Product code : 0334

Other means of identification : Alumina-Silicate Cement Bonded Castable

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory Recommended use : Industrial use

1.3. Supplier

Resco Products. Inc.

One Robinson Plaza, Suite 300

6600 Steubenville Pike

Pittsburgh, PA 15205 - United States

412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300

Outside USA & Canada +1 703-741-5970

### SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### **GHS US classification**

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

H315

Causes skin irritation
H320

Causes eye irritation

Carcinogenicity Category 1A H350 May cause cancer (Inhalation)

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US)

: H315 - Causes skin irritation
H320 - Causes eye irritation
H350 - May cause cancer (Inhalation)

Precautionary statements (GHS US) : P280 - Wear eye protection, Dust respirator, protective gloves.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If skill initiation occurs. Get medical advice/attention.

P260 - Do not breathe dust.

#### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Calcium Aluminate Cement	(CAS-No.) 65997-16-2	20 – 50	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
cristobalite	(CAS-No.) 14464-46-1	20 – 50	Carc. 1A, H350
quartz	(CAS-No.) 14808-60-7	1 – 5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

### **SECTION 4: First-aid measures**

First-aid measures after inhalation

4.1.	Descri	ntion of	f first	aid r	neasures
4.1.	Descii	puon o	ı ııı ət	aiu i	iicasui cs

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse.

07/19/2021 EN (English US) Page 1

Allow affected person to breathe fresh air. Allow the victim to rest.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

First-aid measures after ingestion Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/effects after skin contact Causes skin irritation. Symptoms/effects after eye contact Causes eye irritation. Immediate medical attention and special treatment, if necessary

No additional information available

Symptoms/effects after inhalation

### **SECTION 5: Fire-fighting measures**

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media In case of fire, all extinguishing media allowed.

Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3 Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering

environment.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

**Emergency procedures** : Do not breathe dust.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

**Environmental precautions** 

Prevent entry to sewers and public waters.

Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid raising dust.

Avoid contact with skin and eyes. Do not breathe dust.

Hygiene measures Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

Conditions for safe storage, including any incompatibilities

Storage conditions Store this product in a dry location where it can be protected from the elements.

Incompatible products Strong bases. Strong acids.

#### **SECTION 8: Exposure controls/personal protection**

### **Control parameters**

OSHA PEL (TWA) (mg/m3)

Remark (OSHA)

Rescocast 7 (Mixture)		
No additional information available		
Calcium Aluminate Cement (65997-16-2)		
No additional information available		
cristobalite (14464-46-1)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (mg/m³)	0.025 mg/m³ respirable dust	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) (mg/m³)	0.05 mg/m³ respirable dust	
quartz (14808-60-7)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (mg/m³)	0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)	
USA - OSHA - Occupational Exposure Limits		
Local name	Silica, crystalline quartz, respirable dust	

07/19/2021 EN (English US) 2/5

0.05 mg/m3 respirable dust

(3) See Table Z-3.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Avoid all unnecessary exposure.

### Hand protection:

Wear protective gloves.

### Eye protection:

Chemical goggles or safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Wear appropriate mask

### Other information:

Do not eat, drink or smoke during use.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Granular mixture.

Color : brown
Odor : earthy

Odor threshold : Not applicable

pH : No data available

Melting point : > 2000 °F

Freezing point : Not applicable
Boiling point : Not applicable

Critical temperature : Not applicable
Critical pressure : Not applicable

Flash point : Not applicable
Relative evaporation rate (butyl acetate=1) : Not applicable
Relative evaporation rate (ether=1) : Not applicable
Flammability (solid, gas) : Non flammable.

Vapor pressure : Not Applicable
Vapor pressure at 50 °C : Not Applicable
Relative vapor density at 20 °C : No data available

Relative density : ≈ 1.5

Solubility Slightly soluble. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : Not applicable Decomposition temperature : No data available Viscosity, kinematic No data available Not Applicable Viscosity, dynamic **Explosion limits** Not applicable Explosive properties No data available Oxidizing properties No data available

#### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Hydraulic setting.

### 10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

### Not established.

10.4. Conditions to avoid

Avoid dust formation.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

No additional information available

07/19/2021 EN (English US) 3/5

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to rederal register / vol. //, rvc. 55 / Monday, Ma	<u> </u>
<b>SECTION 11: Toxicological information</b>	
11.1. Information on toxicological effects	
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes eye irritation.
Respiratory or skin sensitization	: Not classified : Not classified
Germ cell mutagenicity Carcinogenicity	: Not classified : May cause cancer (Inhalation).
quartz (14808-60-7)	. Iviay cause cancer (illinatation).
IARC group	1. Carainagania ta humana
	1 - Carcinogenic to humans  : Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Potential Adverse human health effects and	Based on available data, the classification criteria are not met.
symptoms	
Symptoms/effects after inhalation	: May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure
Symptoms/effects after skin contact	through inhalation.  : Causes skin irritation.
Symptoms/effects after eye contact	: Causes skill irritation.
SECTION 12: Ecological information	- Caucas of a minuteria
j	
12.1. Toxicity  No additional information available	
12.2. Persistence and degradability	
Rescocast 7 (Mixture)	
•	N. C. C. P. L. L.
Persistence and degradability	Not established.
cristobalite (14464-46-1)	
Persistence and degradability	Mineral. Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
BOD (% 01 1110D)	Not applicable
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
	11οι αρριιοαυίο
12.3. Bioaccumulative potential	
Rescocast 7 (Mixture)	
Bioaccumulative potential	Not established.
cristobalite (14464-46-1)	
Bioaccumulative potential	No data available.
•	140 data avaiiabie.
quartz (14808-60-7)	
Bioaccumulative potential	No data available.
12.4. Mobility in soil	
cristobalite (14464-46-1)	
Ecology - soil	No data available.
12.5. Other adverse effects	Nana kaawa
Effect on the global warming	None known
Other information	: No other effects known.
<b>SECTION 13: Disposal considerations</b>	
13.1. Disposal methods	
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

07/19/2021 EN (English US) 4/5

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 14: Transport information**

**Department of Transportation (DOT)** 

In accordance with DOT

Not regulated

**Transportation of Dangerous Goods** 

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

#### Rescocast 7 (Mixture)

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

### Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

#### cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

**National regulations** 

### quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

#### 15.3. US State regulations

cristobalite (14464-46-1)

Rescocast 7 (Mixture)	
U.S California - Proposition 65 - Other	This product contains crystalline silica, a chemical known to the state of California to
information	cause cancer. For more information go to WWW.P65Warnings.ca.gov

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		
quartz (14808-6	0-7)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date 07/19/2021

Report language name. English. In the event of any conflict between English and other Other information

language versions, the English version shall prevail.

#### Full text of H-phrases:

H315	Causes skin irritation	
H320	Causes eye irritation	
H350	May cause cancer	

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.

07/19/2021 EN (English US) 5/5